

Index

- 5G, 1
- 64 QAM, 139
- 6G, 1
- air mass, 23
- ambient backscattering, 173
- ambient electromagnetic energy, 110
- antenna far-field, 122
- antenna oscillator, 105
- ASTM, 23
- backscatter communication, 170
- battery, 158
 - C-rate, 160
 - capacity, 160
- Bequerel, E., 21
- bimorph, 53
- Bode and Fano, 124
- boost converter, 148
- Brown, W. C., 99
- cantilever, 53
- capacitor, inkjet printed, 17
- carbon nanotube, 15
- Carnot efficiency, 64
- characteristic equation, 94
- class-F
 - rectifier, 105
- CMOS, 163
- coefficient
 - Peltier, 59
 - Seebeck, 59
 - Thomson, 60
- coffee ring, 15
- coil
 - misalignment, 87
- Colpitts oscillator, 138
- complementary cumulative distribution function (CCDF), 135
- conduction, 61
- continuous conduction mode (CCM), 148
- continuous wave, 135
- convection, 61
- conversion efficiency, 117
- coupled resonator theory, 84
- coupling coefficient, 52, 80, 87
- cross-linking, 15
 - heat, 15
 - UV, 15
- current responsivity, 114
- damping factor, 50
- detailed balance limit, 26, 31
- Dickinson, 99
- diode
 - breakdown voltage, 116
- diode rectifier, 101
- discontinuous conduction mode (DCM), 148, 152
- efficiency
 - amplifier, 75
 - aperture, 76
 - rectifier, 76
- efficiency, TEG, 64
- electric generator model, 47
- electromagnetic interference, 98
- elergy harvester
 - piezoelectric, 53
- energy harvesting
 - electromagnetic, 110
 - kinetic, 44
 - RF, 76
 - solar, 21
- energy storage, 142, 158
- figure of merit, thermoelectric material, 67, 68
- fill factor, 32
- Fourier's law, 62
- generation, solar cell, 22
- Glaser, 99
- Goldstone, 99
- graphene, 15
- Hamill, 105
- harmonic balance, 122, 127
- heat diffusion equation, 64
- helicopter, 99

- HEMT, 106
- HVAC, 44
- illuminance, 23
- impedance matching, 86
- inductive coupling
 - measurements, 89
 - nonresonant, 79
 - resonant, 81
- inkjet printing, 6
 - continuous, 7
 - drop-on-demand, 7
- instantaneous power variance, 139
- Internet of Things, 1, 5, 163
- irradiance, 23
- Jet Propulsion Laboratory, 107
- Kelvin relationships, 60
- kinetic energy transducer, 44
 - electromagnetic, 46
 - electrostatic, 45
 - piezoelectric, 47
- Kirchoffs law, 93
- Kyoto University, 99
- Lambert function, 33, 119
- laser beam, 108
- linear regulator, 145
 - series, 146
 - shunt, 146
- Marconi, G., 2
- maximum power point tracking (MPPT), 166
- MEMS, 53
- metamaterial arrays, 94
- Mica, 1
- microcontroller, 164
 - active mode, 167
 - clock frequency, 167
 - hibernate mode, 168
 - low power, 166
 - power saving mode, 167
- milling, 10
- modified Bessel function, 119
- mutual inductance, 80, 89
- nanowire, 16
- natural modes, 94
- Ohm's law, 62
- open-circuit voltage, 29, 122
- operational amplifier, 145
- oscillator, 156
- Paradiso, 54
- parasitic resistance, 30
 - parallel, 30
 - series, 30
- particle swarm optimization, 97
- peak-to-average-power ratio (PAPR), 136
- pellet, 60
- Peltier effect, 59
- phased array, 95, 99
- photoconductor, 22
- photodiode, 22
- piezoelectric, 16
 - nanowire, 16
- Planck's distribution, 25
- polymer, 14
- power converter, 142
 - linear, 142, 145
 - step down, 144
 - switched mode, 142
- power density, 110
- power management unit, 164
- power supply, 142
- power transfer
 - capacitive, 97
- power transfer efficiency, 81, 83
- primary battery, 159
- PVDF, 54
- PZT, 54
- Qi standard, 78
- quality factor, 90
- quantum dot, 22
- Queisser, 25
- Ragone diagram, 159
- rechargeable battery, 159
- reciprocity theory, 121
- recombination, 26, 28, 29
- rectenna, 111
 - angle of arrival, 132
 - class-F, 107
 - nonlinear optimization, 120
- rectifier, 100, 112
 - bidirectional, 106
 - equivalent capacitance, 126
 - equivalent resistance, 126
 - millimeter wave, 107
 - multiband, 124
 - optimum input resistance, 120
 - optimum load, 120
 - Schottky diode, 115
 - transistor, 106
 - Wilkinson, 133
- regulator
 - Zener, 157
- relay resonators, 94
- resistance compression circuit, 130
- resistive divider, 146
- RFID, 1, 163, 170
 - bistatic configuration, 171
 - reference range, 171
 - transmission coefficient, 170

- s-parameters, 121
- secondary battery, 159
- Seebeck effect, 58
- Seiko, 55
- self-inductance, 89
- sensing
 - antenna-based, 168
- sheet resistance, 13
- Shenk, 54
- Shockley, 25
- short-circuit current, 29
- signal optimization, 135
- silver nanoparticle ink, 13
- sintering, 11
 - laser, 12
 - thermal, 11
 - UV plasma, 12
- smart dust, 1
- software-defined radio, 97
- solar antenna, 38
 - PET, 39
 - slot, 39
 - textile, 39
- solar power satellite, 78, 99
- solar rectenna, 38
- solar RFID, 39
- specific energy, 158
- specific power, 158
- spectral irradiance
 - direct and circumsolar, 23
 - global, 23
- spectrum analyzer, 136
- SPICE model, TEG, 69
- strong coupling
 - double peak, 84
- SU-8, 15
- supercapacitor, 158
 - equivalent circuit, 161
- surface energy, 10
- switch, 102
 - SPDT, 147
 - SPST, 147
- switched mode power converter, 155
 - input resistance, 143
 - boost, 147
 - buck, 147
 - buck-boost, 147
 - efficiency, 143
 - flyback, 147
 - steady-state analysis, 147
 - step-down, 147
 - step-up, 147
- tandem solar cell, 35
 - series connected, 35
 - unconstraint, 35
- TEG, 58
- Telos, 1
- Tesla, N., 2
- thermal radiation, 62
- thermodynamics
 - first law, 63
- thermoelectric phenomena, 58
- Thevenin equivalent circuit, 121
- Thomson effect, 60
- time reversal duality, 104
- transducer
 - thermoelectric, 58
- transmission coefficient, 52
- ultimate solar cell efficiency, 25
- vector signal analyzer, 136
- vibration sources, 51
- wet etching, 10
- Wheeler formula, 91
- Wilkinson power combiner, 133
- Williams, 47
- wireless communication transceiver, 169
- wireless power transmission, 75
- wireless sensing platform, 163
- WISP, 171
- Yates, 47
- Zener diode, 145